

# KENWOOD

Listen to the Future

## NEXEDGE™

# NX-210

NEXEDGE™ VHF Digital & FM Portable Radio

**NXDN®**

**FleetSync®**  
by KENWOOD



### GENERAL FEATURES

- 5 W (136-174 MHz) Model
- 512 CH-GID / 128 Zones
- 12-Key Keypad Model
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function/Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Volume Knob
- 6 Front PF & Menu Keys
- 2 Side PF Keys
- Emergency/AUX Key
- 500 mW Speaker Audio
- VOX Ready
- Emergency Call Features
- Emergency Man-Down Option
- Lone Worker
- Multi-Language Display
- Programmable TX/RX Indication (On/Off)
- Special Alert Tone Patterns
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Options
- KMC-38GPS Speaker Mic Option
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- Front Panel Test & Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Easy Option Port
- PC Serial Interface
- SDM Manual Input<sup>1</sup>
- Transparent Data Mode<sup>1</sup>
- VGS-1 Voice Guide/Voice & GPS Data Storage Option

### DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging<sup>1</sup>
- Remote Stun/Kill<sup>1</sup>
- Remote Check<sup>1</sup>
- Short & Long Data Messages<sup>1</sup>
- GPS Location with Voice<sup>1</sup>
- NXDN® Scrambler Included (Conventional: per CH)

### DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- DTMF (Encode/Decode)
- Individual & Group Selective Call
- Caller ID Display
- Mixed FM/Digital Operation

### DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call
- Broadcast Call
- Transmission Trunked Mode<sup>2</sup>
- Message Trunked Mode<sup>2</sup>
- Call Queuing with Priority<sup>2</sup>
- Call Queue Pre-emption<sup>2</sup>
- Late Entry (UID & GID)<sup>2</sup>
- 4 Priority Monitor ID's<sup>2</sup>
- Remote Group Add<sup>1</sup>
- Failsoft Mode
- Multi-Site IP Network Compatible

### SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

### FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- FleetSync®/II
- DTMF Encode / Decode
- Companded Audio
- Voice Inversion Scrambler
- Encryption/ANI Board Control

### FM CONVENTIONAL ZONES

- QT / DQT
- Two-Tone Decode
- Single/Two-Tone Encode
- Call Key 1-6
- Operator Selectable Tone

### FM LTR® TRUNKED ZONES

- Kenwood LTR® Features

### FleetSync®/II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging<sup>1</sup>
- Emergency Status
- Caller ID Display
- Short Text Messages<sup>1</sup>
- Power On/Off Status Messages<sup>1</sup>
- Send/Display GPS (KMC-38GPS)<sup>1</sup>
- PTT ID & Emergency GPS Reporting<sup>1</sup>
- Status Message Block GPS Reporting<sup>1</sup>

## Options

### ■ KNB-31A

Ni-Cd Battery (1700mAh)

### ■ KNB-32N

Ni-MH Battery (2500mAh)

### ■ KNB-33L

Li-ion Battery (2000mAh)

### ■ KNB-43L

Li-Polymer Battery (3300mAh)

### ■ KNB-49PL

Primary Lithium Battery (4500mAh)

### ■ KBP-6

Alkaline Battery Case

### ■ KSC-32

Rapid Rate Charger for Ni-Cd/Ni-MH/Li-ion



KNB-33L



KBP-6



### ■ KSC-326

Rapid Rate Six Unit Charger for Ni-Cd/Ni-MH/Li-ion

### ■ KVC-15

Rapid Rate Vehicular Charger Adapter for KSC-32

### ■ KVC-18

D.C. Vehicular Charger

### ■ KRA-22

VHF Helical Antenna

### ■ KRA-26

VHF Whip Antenna

### ■ KRA-16

VHF Stubby Antenna

### ■ KRA-25

VHF High Gain Antenna



### ■ KMC-41M

MIL-STD & IP 54/55 Speaker Microphone

### ■ KMC-38GPS

GPS Speaker Microphone

### ■ KEP-1

Heavy Duty Earphone

### ■ KHS-11BL

2-Wire Mini Lapel Mic. with Earphone

### ■ KHS-12BL

3-Wire Mini Lapel Mic. with Earphone

### ■ KHS-14

Lightweight Single Muff Headset



### ■ KHS-15-BH

Over-the-Head Heavy Duty Headset

### ■ KHS-15-OH

Behind-the-Head Heavy Duty Headset



### ■ VGS-1

Voice Guide & Storage Unit



### ■ KBH-11

Belt Clip (2.5")



### ■ KLH-154K2

Heavy Duty Leather Carrying Case



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

## Main Specifications

		NX-210
<b>GENERAL</b>		
Frequency Range		136-174 MHz
Number of Channels		512
Zones		128
Max. Channels per Zone		250
Channel Spacing	Analog/Digital	12.5 / 15 / 25 / 30 kHz (6.25 / 12.5 kHz)
Operating Voltage		7.5V DC ± 20%
Battery Life (5-5-90)	with KNB-31A with KNB-32N with KNB-33L	More than 10 hours More than 14 hours More than 11 hours
Battery Life (10-10-80)	with KNB-31A with KNB-32N with KNB-33L	More than 6 hours More than 9 hours More than 7 hours
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)
Frequency Stability		± 2.0 ppm
Antenna Impedance		50 Ω
Dimensions (W x H x D)	Radio only with KNB-31A with KNB-32N with KNB-33L	2.28 x 5.46 x 0.88 in (58 x 138.8 x 22.4 mm) 2.28 x 5.46 x 1.60 in (58 x 138.8 x 40.7 mm) 2.28 x 5.46 x 1.60 in (58 x 138.8 x 40.7 mm) 2.28 x 5.46 x 1.35 in (58 x 138.8 x 34.2 mm)
Weight (net)	Radio only with KNB-31A with KNB-32N with KNB-33L	9.52 oz (270 g) 18.52 oz (525 g) 19.58 oz (555 g) 13.93 oz (395 g)
FCC ID		ALH423500
IC Certification		282D-423500

		NX-210
<b>RECEIVER</b>		
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)	0.20 μV 0.25 μV 0.25 μV
Selectivity	Analog @ 25 kHz Analog @ 12.5 kHz	72 dB 65 dB
Intermodulation Distortion	Analog	70 dB (±50,100 kHz)
Spurious Response	Analog	70 dB
Audio Distortion		Less than 3%
Audio Output		500 mW / 8 Ω
<b>TRANSMITTER</b>		
RF Power Output		5 W / 1 W
Spurious Response		70 dB
FM Hum & Noise	Analog @ 25 kHz Analog @ 12.5 kHz	45 dB 40 dB
Audio Distortion		Less than 3%
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync™ is a registered trademark of Kenwood Corporation.  
LTR™ is a registered trademark of Transcript International.  
AMBE+2™ is a trademark of Digital Voice Systems Inc.  
Windows™ is a registered trademark of Microsoft Corporation.  
NXDN™ is a trademark of Kenwood Corporation and Icom Inc.  
NEXEDGE™ is a trademark of Kenwood Corporation.

## Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
<b>International Protection Standard</b>				
Dust & Water Protection	IP54/55			

footnotes from Front:

<sup>1</sup> Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).  
<sup>2</sup> These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

## Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood U.S.A. Corporation  
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.  
Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



www.kenwoodusa.com



ADS#11209 Printed in USA